

MRO 1016 – ANTI TRACK KOTE

Air Drying Class ‘H’ Anti Track Coating

PRODUCT DESCRIPTION

‘MRO 1016 – ANTI TRACK KOTE’ and protective varnish is a coating with exceptional insulating properties for electrical and electronic equipment to provide surface protection against oils, water, moisture, corrosion, acids, alkalis & temperature variations.

Dry to touch in 15 minutes after application, and tack free within 60 minutes, this fast air drying, flexible coating has excellent adhesion to metal windings and coils with a temperature Class H (180°C) rating and high dielectric strength.

‘MRO 1016 – ANTI TRACK KOTE’ offers complete surface protection by sealing out water and moisture while possessing excellent penetrating and adhesive properties along with resistance to oils.

BENEFITS

- Possesses high dielectric strength, surface and volume resistivity to provide effective insulation of electrical equipment
- Hard, durable & flexible protective film does not peel, crack or age and offers protective resistance to shocks, abrasion as well as aggressive chemical environments
- Fast air-drying, stable, single component coating with excellent resistance against oils, chemicals, ageing, moisture condensation, weathering effects
- Seals out moisture with a visible, highly glossy, smooth abrasion resistant protective coating
- Highly heat resistant coating suitable for Class H insulation with greater allowance for thermal expansion and contraction
- Prevents tracking, corona discharges, flashovers and electrical failures caused by water seepage
- Very good adhesion on a variety of substrates
- Oil resistant to ASTM D 115



APPLICATIONS

Use ‘MRO 1016 – ANTI TRACK KOTE’ protective coating to insulate and seal:

- Armatures
- Bus bars
- Ceramic, Epoxy & plastic insulators
- Commutator ends
- End turns on electrical windings
- Generators
- Insulator bushes
- Motor windings
- Rewound motors
- Stator coils
- Terminals
- Transformers

Highly suitable for insulating electrical windings that are exposed to extreme moisture and corrosive conditions as well as temperature and voltage fluctuations

DIRECTIONS FOR USE

Shake can well before use. Clean thoroughly and dry the surface to be coated before application of this coating. Mask area not to be sprayed. Spray from 12-15 inches away in light, even coats with a sweeping action of the hand. Allow solvents to evaporate completely before re-application. Additional coats for heavy film can be applied when first coat is dry. Coating becomes dry to touch in about 20-30 minutes. Clean the valve by inverting the can and spraying a few short bursts till only the clear propellant comes out. Clean the actuator button orifice by means of a thin, fine wire.

CAUTION

It contains flammable solvents and propellant. Do not spray near naked flame, hot surfaces or energized equipment.

GENERAL

Use in well ventilated areas. Avoid continuous breathing of vapour and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product’s safety data sheet (SDS).

SHELF LIFE

24 Months from date of manufacture

AVAILABLE PACKAGING

500 ml/355 gm (Net)/650 ml gross Aerosol Can

MRO 1016 – ANTI TRACK KOTE

Air Drying Class 'H' Anti Track Coating

Technical Properties

PARAMETER	VALUE
Description	Anti track, insulating & protective varnish
Class	H
Type	Fast air drying coating
Adhesion	Excellent
Colour Fastness	Excellent
Solvents	Ketones, Aliphatic
Percent Solids (By Weight)	18 minimum
Odour	Solvent
Appearance	Glossy finish
Specific Gravity @ 20°C	0.90 - 1.05 gm/cc
Flash Point	-18° C
Drying Time Schedule,@ 25°C	
-To Touch	10-15 minutes
-To Handle	30-45 minutes
- Full Cure	24 hours
Recoating Period	After drying to handle
Corrosion Resistance Test	Passes
Resistant To	Mineral oils, mineral spirits, gas, water, humidity
Temperature Range	-40°C to +180°C
Evaporation Rate	> n, butyl acetate
Vapour Pressure (air=1)	>air
Dielectric Strength	2.2 KV/mil (88 KV/mm)
Dry Film Thickness(dft)	25 microns per coat
Stability	Stable under normal conditions
Conditions To Avoid	Keep away from heat and sources of ignition
Chemical Incompatibility	Strong oxidizing agents, alkalis, acids
Propellant	Hydrocarbon
Safety	Does not contain any human carcinogenic substances

HANDLING

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding PPE, safe use, and physical & health hazards. Safety data sheet is available from MRO INFRA or your local MRO INFRA Channel Partner.

DISPOSAL

All used and unused product should be disposed of in accordance with state regulations.

LIMITED WARRANTY

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended MRO INFRA product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty.